查询CNC1H001供应商

CNC1H001

Optoisolator

■ Features

- Housed in a surface mount package alternative to mini-flat package of 1.27 mm pitch
- Double molded package
- 2.5 kV isolation voltage
- UL approved (File No. E79920)

■ Applications

- Suited for interface circuits requiring high density mounting of parts, especially hybrid ICs and programmable controllers
- Signal transfer between circuits with different potentials and with impedances

Unit: mm



1, 3, 5, 7 : Anode
2, 4, 6, 8 : Cathode
9, 11, 13, 15 : Emitter
10, 12, 14, 16: Collector
PCTFG116-001 Package

Pin Connection



■ Absolute Maximum Ratings $T_a = 25°C$

Parameter		Symbol	Rating	Unit
Input (light emitting diode)	Reverse voltage (DC)	V_R	6	V
	Forward current (DC)	I_F	50	mA
	Pulse forward current *1	I_{FP}	1	A
	Power dissipation *2	P_D	75	mW/ch
Output (photo transistor)	Collector current	I_C	50	mA
	Collector-emitter voltage	V_{CEO}	80	V
	Emitter-collector voltage	V_{ECO}	7	V
	Collector power dissipation *3	P_C	120	mW/ch
Isolation voltage, input to output *4		V_{ISO}	2 500	V[rms]
Operating ambient temperature		T_{opr}	−30 to +100	°C
Storage temperature		T_{stg}	−55 to +125	°C

Note) ∗1: Pulse repetition rate = 100 pps. Pulse wide ≤ 100 µs
∗2: Above 25°C ambient temperature, derate dissipation at the rate of 0.75 mW/°C.
∗3: Above 25°C ambient temperature, derate dissipation at the rate of 1.2 mW/°C.
∗4: AC voltage (t = 1.0 min., RH < 60%)

■ Electrical Characteristics $T_a = 25°C \pm 3°C$

Parameter		Symbol	Conditions	Min	Typ	Max	Unit
Input diode	Forward voltage	V_F	$I_F = 50$ mA		1.35	1.5	V
	Reverse current	I_R	$V_R = 3$ V			10	μA
	Capacitance	C_t	$V_R = 0$ V, f = 1 MHz		15		pF
Output transistor	Collector-emitter dark current	I_{CEO}	$V_{CE} = 20$ V		5	100	nA
	Collector-emitter voltage	V_{CEO}	$I_C = 100$ μA	80			V
	Emitter-collector voltage	V_{ECO}	$I_E = 10$ μA	7			V
	Collector capacitance	C_C	$V_{CE} = 10$ V, f = 1 MHz		10		pF
Coupled	Current transfer ratio *1	CTR	$V_{CE} = 5$ V, $I_F = 5$ mA	100		600	%
	Capacitance	C_{ISO}	f = 1 MHz		0.6		pF
	Resistance	R_{ISO}	$V_{ISO} = 500$ V	10^{11}			Ω
	Rise time *2	t_r	$V_{CC} = 10$ V, $I_C = 2$ mA		4		μs
	Fall time *3	t_f	$R_L = 100$ Ω		3		
	Saturation voltage	$V_{CE(sat)}$	$I_F = 20$ mA, $I_C = 1$ mA		0.1	0.2	V

Note) ∗1: CTR = I_C / I_F × 100%

∗2: Rise time is defined as the time required for the I_C to rise from 10% to 90% of peak value.

∗3: Fall time is defined as the time required for the I_C to decrease from 90% to 10% of peak value.

Input and output are practiced by electricity.

The device is designed be disregarded radiation.

P_C , P_D — T_a



I_F — V_F



I_C — I_F



I_C — V_{CE}



ΔI_C — T_a



I_{CEO} — T_a



t_r — I_C



t_f — I_C



Frequency characteristics



⚠ Caution for Safety

⚠ DANGER

■ Gallium arsenide material (GaAs) is used in this product.

Therefore, do not burn, destroy, cut, crush, or chemically decompose the product, since gallium arsenide material in powder or vapor form is harmful to human health.

Observe the relevant laws and regulations when disposing of the products. Do not mix them with ordinary industrial waste or household refuse when disposing of GaAs-containing products.

Request for your special attention and precautions in using the technical information and semiconductors described in this book

(1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technologies described in this book and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.

(2) The technical information described in this book is limited to showing representative characteristics and applied circuits examples of the products. It neither warrants non-infringement of intellectual property right or any other rights owned by our company or a third party, nor grants any license.

(3) We are not liable for the infringement of rights owned by a third party arising out of the use of the product or technologies as described in this book.

(4) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
- Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
- Any applications other than the standard applications intended.

(5) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.

(6) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage, and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.

(7) When using products for which damp-proof packing is required, observe the conditions (including shelf life and amount of time let standing of unsealed items) agreed upon when specification sheets are individually exchanged.

(8) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.

2002 MAY